

Caraquet's sea port data sheet

- **Port's geographic location** : Gulf of St.Lawrence, 40.23 kilometres inside the Bay of Chaleurs. Sheltered harbour.
- **Wharf** : The wharf has a 260 metre mooring façade, a 165-metre Western pier and a 91-metre Eastern pier. The minimum depth along the wharf is 7 metres.
- **The channel** : The channel's minimum depth, at low tide, is 5.5 meters. It is marked with lighted navigation buoys and with 5 localizers.
- **Tides and currents** : The tide ranges from 1.5 metres at high wild water, and 1.2 meters at mean dead water. The current has a velocity of 1.5 knot.
- **Distance between the pilot house and the entry of the wharf** : 24.54 kilometres.
- **Slip way** : Maximum weight : 600 000 kg Approximate length : 45.72 metres
- **Allowed dimensions for boats** : Maximum length : 135 metres. Draught : 6.22 metres. Deadweight : 7 500 000 kg.
- **Available facilities and services** : Electricity, drinking water, saltwater, drainage, mooring service (the port committee is responsible for the mooring of large boats when they arrive and leave) ; pilot services available 24 hours a day.
- **Hydraulic, mechanical, welding services etc. :**
Dugas Équipement Itée, Caraquet
Dugas Fab inc., Caraquet
Industrie Marine, Bas-Caraquet
Les Aciers Forse Steel, Caraquet
- **Fuel supply (diesel or gasoline)** : Esso, Irving, Pétro Canada
- **Ship lift** : Friolet Services Maritimes
- **Maximum weight** : 60 000 to 100 000 kg.
- **Maximum length** : 25.91 metres.
- **Ice :**
Caraquet Ice Ltd.
Les Produits Belle Baie Ltée
- **Existing businesses :**
Carapro
Les Produits Belle Baie Itée
Caraquet Ice
Ichiboshi, L.P.C. Itée

